



MRE[®]
Pioneering Power Supplies



16 Port 180Watt PoE Switch MRE18e(1) Manual

Product Profile

MRE18e(1) is 16 port 10/100M PoE port, 2 Gigabit Uplink port, 2 Gigabit SFP port, unmanaged PoE switch. Auto detection and identification IEEE802.3af/at standard PD device, then carry power to it. Therefore do not worry it will destroy the private standard PoE or Non-PoE equipment.

MRE18e(1) is the best choice for minitype commercial network because it economically use PoE deployment IP camera .

MRE18e(1) can resolve the problem of maintenance tedious, wireless coverage, terminal device powered, surveillance project. Maximum save the cost.

Key Features

- Support power over ethernet cable device for example IP camera
- Support IEEE802.3af/at standard .
- Data and power transmission distance 100m, it can be flexible installation for IP camera.
- Support upward port auto MDI/MDIX.
- Adopted storage forward switch system.
- Smart power and minimum power consumption , guarantee PD requirement.
- With power supply circuit protection function and protection back-end device safety
- Automatically provide the adaptive device
- Adopted dual fan cooling design to guarantee the equipment stability ;
- Support the flow control, 802 x full duplex mode ;
- Support saving power function when port unconnection
- Support maximum 1536 Bytes
- Support control broadcast packets

Specification

Network Port	- 16 port 10/100M PoE RJ45 port (Self-adaptive MDI/MDIX) ;
	- 2 10/100/1000M Non-POE RJ45port(Self-adaptive MDI/MDIX) ;
	- 2 Gigabit SFP port
Network protocol and standard	- IEEE 802.3 10BASE-T
	- IEEE 802.3u 100BASE-TX
	- IEEE 802.3ab 1000BASE-T
	- IEEE 802.3z 1000BASE-X
	- IEEE 802.3x Flow Control
	- IEEE 802.3af/at Power over Ethernet
Power	- Total power : 180Watts
	- PoE power pin : 1,2(+),3,6(-) or 4,5(+),7,8(-)
	- Voltage : 100 -240VAC/48VDC , 3.75A , 50/60 Hz
Network protocol and standard	- Transfer pattern : store-and-forward
	- Bandwidth : 7.2 Gbps (non-blocking)
	- Store and forward mode : network delay (100 Mbps ~ 100 Mbps) : maximum 20 μ s(using 64 byte)
	- Buffer memory : 2.75Mb
	- MAC address : 48 byte physical address
	- Address database size : 4K MAC
LEDs indicator	- Power
	- LINK/ACT
	- PoE
EMC	- CE mark, commercial
	- FCC Part 15 Class A
	- VCCI Class A
	- C-Tick
Radiation/ electromagnetic	- EN 55016
Certifications	- CE mark, commercial
	- UL 60950 (Listed) /EN60950
Environment	- Operating Temperature : 0-50°C
	- Storage Temperature : -40-70°C
	- Operating Humidity : Maximum 90% (Non-condensing)
	- Storage Humidity : Maximum 95% , (Non-condensing)
	- Operating Altitude : Maximum 10,000 feet (3,000 meters)
	- Storage Altitude : Maximum 10,000 feet (3,000 meters)
Dimensions	- MTBF : 300,000 Hours
	- Size (LxWxH) : 283mm x 180mm x 44mm
	- Weight : 2.3kg

LED Instruction

Indicator	Introductions	Normal State	Abnormal and Process
PWR	PWR Indicators	Red Light ON	If red light off, pls check whether the external power supply plug powered normal and whether the power adaptor connect correctly.
PoE	PoE Indicators	Red Light ON	If red light off, pls check whether the corresponding RJ45 access network device and the network cable connect correctly, whether the network cable is accord with Cat.5 standard(transmission distance max. 100meter)、whether the network cable and network device is damaged.
LINK	PD Device Connection	Yellow Light ON	If light off , pls check whether the corresponding RJ45 access network device and PoE powered normal、whether the network cable connect correctly and whether network device is damaged.
ACT	Network status indicator	Green Light ON	If the light condition does not accord with the network status,pls check whether the corresponding RJ45 access network device and PoE powered normal、whether the network cable connect correctly and whether network device is damaged.

Application Suggestion

1. In order to safety , pls non-professionals don't open the casing of product ;
- 2.Pls be careful the risk of strong current and security protection when product is carrying on power ;
- 3.Pls select the right power adaptor provide power for PoE switch , before using pls confirm if is it accord with the requirement of PoE switch ;
- 4.Pls don't use PoE switch under the humid environment , avoiding water go into the product inside caused PoE switch breakdown.
- 5.Pls start the power after the circuit connected ;
- 6.Pls don't plug-in and plug-out the connection cable when product is carrying power ;
- 7.Pls don't use PoE switch under somewhere with more dust and EME;Don't use PoE switch in high temperature and unventilated place;
- 8.Pls don't put heavy thing on PoE switch , in case of happening an accident. ;
- 9.According to IEEE802.3AF/AT standard, pls use the Cat.5 or above , transmission distance reach to 100 m ;
- 10.Pls don't exceed the maximum output power of PoE switch when it connect more than one PD device ;
11. Suggestion PoE switch use for indoor , if you want to use for outdoor, pls install waterproof box